



101187 Telescopic arm 160 1,8m

Description:
Local air pollution capture excluding chemically aggressive fumes and gases.

- Standard construction:**
- all adjustments on the outside
 - aluminium hood with air diverter (yellow)
 - grab handle all around the hood
 - aluminium hood joints (black)
 - cast aluminium swivel joints (black)
 - aluminium and steel mounting swivel (yellow)
 - smooth tube (blue)
 - standard built-in air damper (T1618, T1626 models)
 - black PVC flexible hoses (temperature resistance up to 80°C)
 - standard powder coating

Parameters:

Working range: 1,4 - 1,8 m
Diameter: Ø160 mm
Efficiency: 1000 - 1300 m³/h

- Accessories and options:**
- P07-01-0004 Mounting bracket WS-160
 - P07-01-0013 Mounting bracket WSD-160 (longer version)
 - P08-11-0004 Connection flange diameter 150mm steel
 - P08-11-0005 Connection flange diameter 160mm steel
 - P02-80-0001 MOD-A set including photosensor, hood light kit, light switch, 8m of cable
 - P02-80-0002 MOD-L hood light kit with switch and 8m of cable
 - P02-80-0003 MOD-L2 hood light kit with 2 switches (additional switch for fan or electric damper control), 8m of cable
 - P02-80-0010 Grounding option - all metal parts hood, tubes, mounting swivel connected with grounding wires
 - P02-02-0127 Extended hood diameter 160mm/500mm option (adds to the price of arm or standard hood)

- Spare parts:**
- M03-21-1223 Complete set of black PVC flexible hoses for telescopic arm 160
 - P02-02-0125 Complete hood diameter 160mm/315mm
 - P02-05-0012 Complete spring for telescopic arms

Packing and carton size:

	A = 340
	B = 1540
	H = 380
	weight gross = 23 kg

All dimensions are in mm